

Deco-Lume

Model Number	Number of Lamps	Ballast Type	Nominal Length
WT8115	1-15W	TS,LPF	18¼"
WT8120	1-20W	TS,LPF	24¼"
WQ8130	1-30W	RS,LPF	36¼"
WQH8130	1-30W	RS,HPF	36¼"
WQ8140	1-40W	RS,LPF	48¼"
WQH8140	1-40W	RS,HPF	48¼"

Model Number	Number of Lamps	Ballast Type	Nominal Length
WTH8117	1-17W	T8/SSB	24¼"
WQH8125	1-25W	T8/SSB	36¼"
WQH8132	1-32W	T8/SSB	48¼"

Options & Accessories

Model Number	Description
B1	Emergency Battery Pack
W	277 volt (for HPF fixtures only)

SPECIFICATIONS

HOUSING: Entire construction rigidly die-formed of code gauge steel.

SHIELDING: Acrylic white diffuser for soft and even glare-free illumination. Easily installed and removable for re-lamping.

FINISH: All metal parts are cleansed by a multi-stage process and treated with an iron phosphate coating to improve paint adhesion and rust resistance, then electrostatically sprayed with white enamel and baked at 320°F. Minimum of 88% reflectivity.

ELECTRICAL: All units wired with ballasts incorporating Class P thermal protection, for 120 volt, 60 cycle AC current. Ballasts mounted in direct contact with housing for maximum heat dissipation. Sockets completely wired.

INSTALLATION: Units may be surface mounted, individually or in continuous rows. Specify number of fixtures per row when installed in continuous rows.

LABELS: U/L listed combined with I.B.E.W.

