

Designer

T8/SSB,
RS/HPF & TS/LPF

Stilite



Model Number	Number of Lamps	Ballast Type	Nominal Length
T7115	1-15W	TS,LPF	18¼"
TH7115	1-15W	TS,HPF	18¼"
T7120	1-20W	TS,LPF	24¼"
TH7120	1-20W	TS,HPF	24¼"
Q7130	1-30W	RS,LPF	36¼"
QH7130	1-30W	RS,HPF	36¼"
Q7140	1-40W	RS,LPF	48¼"
QH7140	1-40W	RS,HPF	48¼"
T7215	2-15W	TS,LPF	18¼"
TH7215	2-15W	TS,HPF	18¼"
T7220	2-20W	TS,LPF	24¼"
TH7220	2-20W	TS,HPF	24¼"
Q7230	2-30W	RS,HPF	36¼"
Q7240	2-40W	RS,HPF	48¼"

Model Number	Number of Lamps	Ballast Type	Nominal Length
TH7117	1-17W	T8/SSB	24¼"
TH7217	2-17W	T8/SSB	24¼"
QH7125	1-25W	T8/SSB	36¼"
QH7225	2-25W	T8/SSB	36¼"
QH7132	1-32W	T8/SSB	48¼"
QH7232	2-32W	T8/SSB	48¼"

OPTIONS & ACCESSORIES

Code	Description
K	grounded convenience outlet
M	turn knob
R	pull chain
B1	Emergency battery pack
W	277 volt (for HPF fixtures only)

Accessories rated for use with 120 volt ballast only.

SPECIFICATIONS

HOUSING: Entire construction rigidly die-formed of code gauge steel.

SHIELDING: Acrylic white diffuser for soft and even glare-free illumination. Easily installed and removable for re-lamping.

FINISH: All metal parts are cleansed by a multi-stage process and treated with an iron phosphate coating to improve paint adhesion and rust resistance, then electrostatically sprayed with white enamel and baked at 320°F. Minimum of 88% reflectivity.

ELECTRICAL: All units wired with ballasts incorporating Class P thermal protection, for 120 volt, 60 cycle AC current. Ballasts mounted in direct contact with housing for maximum heat dissipation. Sockets completely wired.

INSTALLATION: Units may be surface mounted, individually or in continuous rows. Specify number of fixtures per row when installed in continuous rows.

LABELS: U/L listed combined with I.B.E.W.



Duray Fluorescent Manufacturing Company, Inc.

2050 West Balmoral Avenue Chicago, Illinois 60625 Phone 773.271.2800 Fax 773.271.4410 www.durayinc.com

10/03

1 & 2 LIGHTS WITH SMOOTH WHITE ACRYLIC PLASTIC DIFFUSER

